



## DLF800IRC Thermographic IR Camera



Designed to be in 4 modes: thermal, fusion, visible light, picture in picture.

By thermal mode, the people behind the fog can be searched and rescued; By Fusion, more details or relative location of the human behind the fire can be shown; the picture taken under the visible light will more easily capture these exit, fire hydrants in fire disaster and other objects which the thermal cannot detect; By picture in picture, more information can be shown at the same time for quick judgement and decision in rescue.



People's eye



Fusion

Thermal



Picture in picture


IR color



**Feature:**

1. 4 modes: thermal, fusion, visible light, picture in picture;
2. In thermal mode, there are 21 kinds of IR color (white hot, black hot, red hot, iron red, green hot, etc) for different surroundings;
3. Warning of the preset temperature ( max, min, interval);
4. Touch screen;
5. Automatic or manual adjustment of contrast;
6. laser pointer to indicate the location of the human behind the fire;
7. Temperature measured range is -20°C--+550°C;

8. Two options for temperature:  $-20^{\circ}\text{C}$  --  $+150^{\circ}\text{C}$  and  $+100^{\circ}\text{C}$  --  $+550^{\circ}\text{C}$ ;
9. Emissivity: 0.01-1.00; quick selection for human skin, cable, cement or concrete, pottery, painting, rubber, woods, soil, sand, bricks, papers, etc;
10. Measure the temperature distance: 0-999 meters;
11. Measure the temperature of the target in FRAME which can be set by touching the screen; there can be max, min and average temperature in the frame;
12. Measure the temperature of the target by LINE which can be set by the touching screen, there can be max, min and average temperature in the line;
13. Auto tracking the max and min temperature and show them on the left;
14. Set the point for measuring the temperature and 10 points can be set at the same time;
15. All these temperature can be deleted quickly by touch;
16. The picture can be edited, texted manually in the device;
17. Distance of fusion can be preset: 1m, 2m, 4m,  $>5\text{m}$ ;
18. The ratio of the picture in picture can be % 35-70%;
19. The sound warning can be switched on or off;
20. CVBS out put;
21. The trigger behind can work as the button for taking picture or recording the video;
22. The flashlight can be switched on when taking the picture;
23. High, medium, low brightness adjustment;
24. Degree centigrade, Fahrenheit degree, Kelvin;
25. Inch and meters can be selected;
26. Time and date can be set;
27. Built-in illuminator in visible light;
28. Automatic switching off in preset time: 10/20/30/40/50/60 minutes;
29. WIFI for connecting the other smart devices (APP) and it can work as the 4G transmitter to connect with other computer (phone) for real time transmission;



31. Bluetooth for transferring the sound document to other device;



**Specification:**

<b>Thermal</b>	Sensor	VOX			
	Resolution	384 × 288			
	Spectrum	8~14μm			
	NETD	< 50mk(@25°C,F#=1.0)			
	Focus length	15mm	7.5mm	30mm	50mm
	MRAD	1.13	2.27	0.57	0.34
	FOV	25°× 19°	47°× 34°	12°× 9°	8°× 2°
	F number	F1.0			
	Zoom	1X,2X,4X			
	Frame rate	60HZ			
<b>Visible</b>	3.20 mega pixel, CMOS, Built-in LED illuminator				
<b>Display</b>	Display	3.5”TFT color LCD, 640×480 touch screen			
	Image color	21IR color			
	Mode	Thermal, visible, fusion, picture in picture			
<b>System</b>	Temperature measuring	-20°C~1500°C			
	Accuracy	±2°C or ±2%,			
	Laser pointer	Indicating the location of target			
	memory	64G			
	recording	yes			
	Flash light	yes			
	WIFI	yes			
	Bluetooth	yes			
	AP hot point	yes			
	Text note	yes			
<b>Battery</b>	Voice	60 second voice recording and saved with picture			
	Battery	Lithium battery ( 2 pieces)			
	Working time	4 continuous hours			
<b>Port</b>	Charger	Smart charger (AC adaptor or vehicle 12V)			
	Port	Micro USB, SD slot			
	Working temperature	-20~50°C			
	Protection	IP66			
	Drop proof	2m			
	Dimension(L x W x H)	245×100×105mm			

	Weight	680g
	Accessory	charger, SD card, data cable, suitcase

**Picture of rechargeable Battery:**

